

DT 75/30

RX 75/10

RG 59 B/U

DT 59/8

Applicazioni

Applications

DT 75/30

Trasmissione dati
Data transmission

Video

CCTV

RX 75/10

Trasmissione dati
Data transmission

Video

CCTV

RG 59 B/U

Trasmissione dati
Data transmission

Video

CCTV

DT 59/8

Trasmissione dati
Data transmission

Video

CCTV


Conduttore interno
Inner conductor

CW 1 x 0.40
ø = 0.40 mm

Cu 7 x 0.20
ø = 0.60 mm

CW 1 x 0.58
ø = 0.58 mm

CW 1 x 0.58
ø = 0.58 mm

Materiale isolamento
Insulation material

PE
ø = 2.50 mm

PE
ø = 3.70 mm

PE
ø = 3.70 mm

PE
ø = 3.70 mm

Schermo
Shield

Cu

Cu

Cu

Cu


Guaina
Jacket

PVC
ø = 4.00 mm

PVC
ø = 6.10 mm

PVC
ø = 6.15 mm

PVC
ø = 6.15 mm

Peso
Weight

25 kg/km

50 kg/km

46 kg/km

45 kg/km


Impedenza caratteristica
Characteristic impedance

75 ± 3 Ω

75 ± 3 Ω

75 ± 3 Ω

75 ± 3 Ω


Capacità
Capacitance

67 nF/km

67 nF/km

67 nF/km

67 nF/km


Velocità di propagazione
Propagation velocity

66%

66%

66%

66%


Attenuazione dB/100 m
Attenuation dB/100 m

5 MHz

3.70

2.50

2.20

2.20

10 MHz

5.20

3.60

3.20

3.20

50 MHz

11.50

8.10

7.90

7.90

100 MHz

16.50

12.20

11.20

11.20

200 MHz

25.00

17.10

16.10

16.10

400 MHz

36.00

24.30

23.30

23.30

1000 MHz

58.40

41.50

39.40

39.40